


IKON

IKL60 Barrier Louvre



Product description

Designed to cover areas where fall from height is an issue

60mm twin wall Brise Soleil extruded aluminium blades

Fully welded 63mm X 38mm X 3.2mm outerframe

Pitch—can be varied project specific

Blade angle—can be varied between 45 and 90 degree

Maximum free area varies depending on blade angle and pitch

Standard and special RAL or BS colours available

Product testing

*Impact resistance to BS EN 13049:2003 achieving Class 5 (Wintech Report No R14340-2)

~Impact resistant to BS6180:2011- Building Regulation Approved Part K2 (BRE Report No's P118151-1000 & P118151-1001)

Wind resistance to BS EN12211:2000 and BS EN 12210:2000 achieving Class 4, tested project specific to 2210 pascals.

*Impact resistance BS EN 13049:sample 1000 x 2500, 60mm pitch 45 degree angle

~Impact resistance BS 6180: sample 1200 x 2500, 60mm pitch 45 and 90 degree angle

#Wind resistance sample 1200 x 2850, 60mm pitch 45 degree angle

Unit 1-3 Yardley Brook Industrial Park, Leaford Way, Shard End, Birmingham, B33 9TX

Tel: 0121 789 9936, Fax 0121 783 7905, Web : www.ikonaluminium.co.uk, Sales : info@ikonaluminium.co.uk