


IKON

IKL50 Stackable Louvre



Stacking can be achieved using most outerframe sections

Product description

Stackable louvre panels.

Frames have jamb, head and cill outerframes. Intermediate sections are jointed and connected with spigots and jointing plates as necessary. This gives the appearance of a continuous full height louvre. Louvre segment size to be determined with the customer on a project specific basis. Louvre panels can be made demountable.

Blade Centre 50mm . Blade angle 45 degree.

Visual free area 79%. Physical free area 50%.

Louvre element tested to EN 13030:2002

BSRIA Test report 54729/1

Results of testing of the louvre element only shown

Options

Standard RAL or BS colours. Anodizing to special order.

Drainage channel, insect mesh, bird mesh


Single skin, or double skin insulated blanking panels.

K factor 14.23

Ce 0.265

Watertightness	%	Class	Pressure Drop	Pd
Velocity 0.0	99.4	A	Face Velocity 0.5	2.13
0.5	98.8	B	1.0	8.54
1.0	97.0	B	1.5	19.21
1.5	92.3	C	2.0	34.15
2.0	86.8	C	2.5	53.36
2.5	76.1	D	3.0	76.84

Performance: airflow, louvre with insect mesh



Unit 1-3 Yardley Brook Industrial Park, Leaford Way, Shard End, Birmingham, B33 9TX

Tel: 0121 789 9936, Fax 0121 783 7905, Web : www.ikonaluminium.co.uk, Sales : info@ikonaluminium.co.uk

Issue 2—05/01/26